

# FF 1650 SPECIFICATIONS & STANDARD LIST

SPECIFICATIONS:	
<b>Max people</b> 5 <b>Overall Hull Length</b> 5.40m <b>Length on Trailer</b> 6.10m* <b>Height on Trailer</b> 2.10m* (top windscreen) <b>Width on Trailer</b> 2.14m	<b>Beam</b> 2.14m <b>Deadrise</b> (at transom) 13° <b>Fuel Capacity</b> 70L <b>Water Capacity</b> N/A <b>Dry Towing Weight</b> 1,200kg** (approx.)
<b>Standard Engine</b> Mercury 90 ELPT <b>Maximum Horsepower</b> Mercury 90 ELPT <b>Maximum Weight on Transom</b> 165kg <b>Standard Mackay Trailer</b> MLKR-47-13-M <b>Trailer Weight Rating</b> 1,480kg	
CONVENIENCE STANDARD	
<ul style="list-style-type: none"> <li>Factory Supplied Owner's Manual</li> <li>Anchor Light LED</li> <li>Navigation Lights LED</li> <li>Front S/S Eye Bolt</li> <li>Separate Self Draining Anchor Locker</li> <li>Stainless Steel Split Bow Rails</li> <li>Integrated Rear Moulded Outboard Well</li> <li>70 L Fuel Tank (With Fuel Sender)</li> <li>Fibreglass Encapsulated Stringer System</li> <li>Foam Filled Hull</li> <li>Local Registrations (Where Available) (Boat &amp; Trailer)</li> </ul>	<ul style="list-style-type: none"> <li>Recessed Side Cabin Windows (Tinted)</li> <li>3 x Rear Darin Plugs</li> <li>2 x Windscreen Grab Handles</li> <li>Rubber Side Steps (with Whittley Logo)</li> <li>Australian Builders Plate</li> <li>Whittley Warning Label Kit</li> <li>5 Year Hull Warranty</li> <li>*Refer Full Warranty Policy for more information</li> <li>Victorian Inshore Safety Equipment &amp; Accessory Kit</li> <li>Freight &amp; Local Delivery Charges (To Closest Australian Capital City)</li> </ul>
INTERIOR STANDARD	
<ul style="list-style-type: none"> <li>Moulded Black Dash Board</li> <li>Whittley Rubber Flooring Throughout</li> <li>Front Cabin Side Cushions</li> <li>2 Rear Quarter Removable Seats</li> <li>S/S Rear Grab Handles</li> </ul>	<ul style="list-style-type: none"> <li>Sports Steering Wheel</li> <li>Front Under Bunk Storage</li> <li>Side Pocket Cabin Storage</li> <li>Sports Driver &amp; Passenger Seats (Adjustable Drivers Position)</li> </ul>
EXTERIOR STANDARD	FISHING STANDARD
<ul style="list-style-type: none"> <li>Vynlester Blend Gel Coat for Superior Finish &amp; Longevity</li> <li>Folding Front Hatch</li> <li>Moulded Integrated Bow Sprit</li> <li>Whittley Front Bow Roller</li> <li>Moulded Rear Boarding Platforms</li> <li>S/S Rear Folding Boarding Ladder</li> <li>S/S Boarding Rails</li> <li>Rear Tow Points</li> <li>White Hull</li> <li>Tough Rubber Gunnel Fender Strip</li> <li>Sports Whittley Decal Kit</li> <li>2 x S/S Mooring Cleats</li> <li>S/S Split Front Bollard</li> <li>Fibreglass Moulded Gunnel Caps</li> <li>S/S Fuel Filler &amp; Cap</li> </ul>	<ul style="list-style-type: none"> <li>Moulded Bait Well (With Folding Lid)</li> <li>4 x S/S Flush Mount Rod Holders</li> <li>Carpeted Side Pockets</li> <li>Full Length Rod Storage in Side Pockets</li> <li>Fish Measuring Ruler Cut into Rubber Flooring</li> </ul>
ELECTRICAL STANDARD	CANOPY STANDARD
<ul style="list-style-type: none"> <li>Waterproof Switch Panel</li> <li>Raised Battery Storage</li> <li>Automatic Bilge Pump</li> <li>Tinned Marine Grade Wire Throughout</li> <li>Battery Tray &amp; Marine Grade Battery</li> </ul>	<ul style="list-style-type: none"> <li>Custom Fitted Sports Bimini</li> </ul>
ENGINE STANDARD	TRAILER STANDARD
<ul style="list-style-type: none"> <li>Mercury 90 ELPT Stroke Model</li> <li>Mechanical Steering System</li> <li>Sports Steering Wheel</li> <li>Mercury Control Box</li> <li>Mercury Gauges</li> <li>Mercury Switch Panel</li> <li>Mercury Water Fuel Filter</li> <li>Mercury Control Cables</li> <li>Mercury Black Max Alloy Prop</li> </ul>	<ul style="list-style-type: none"> <li>Mackay Trailer Model # MLKR-47-13-M</li> <li>Factory Spec Mackay Galvanised Single Axle Trailer</li> <li>Spare Wheel</li> <li>Spare Wheel Cover</li> <li>Trailer Bunk Rollers</li> <li>Keel Ladder Support</li> <li>Drive On – Drive Off Feature</li> <li>High Quality Jockey Wheel</li> <li>Front &amp; Rear Deluxe Ratchet Straps</li> </ul>

## SPECIFICATION & STANDARD EQUIPMENT PRODUCT SHEET DISCLAIMER:

Every effort has been made to ensure that the information on this document is correct and up to date. However, Whittley Marine Group Pty Ltd ACN 6279 33635 ("Whittley") does not provide any warranty as to the completeness or accuracy of the information and subject to applicable laws, does not accept any liability for damages of any kind resulting from the access or use of this content. This document & information is produced as a guide only, please consult the Whittley web-site for further information or your local dealer before using this information as a deciding factor to purchase.

\* The height and length on trailer measurement can be reduced or lowered upon request. For example, a swing away draw bar option is available to reduce the overall length. Please talk to your local dealer for more information. The measurements supplied are to be used as a guide only and may vary from time to time. Weights and measurements listed in this catalogue are as occur as can reasonably be determined and can be subject to change. Weights and measures are approximate only and are considered a guide these can vary up to plus 15%.

Whittley does not take any responsibility for weights and measurement accuracy therefore these should be checked by the dealer or customer if this is a requirement that is deemed critical for the use or before purchase of any vessel. To confirm the measurements before making a purchase, consult your Authorized Whittley Dealer or Whittley Factory Sales Representative.

\*\* Dry towing weight is an approximate guide and is a best-case scenario, this may vary and is the approximate base package weight with no options. The addition of factory supplied options will increase the total Boat Motor Trailer (BMT) package weight. Consult your Authorized Whittley Dealer or Whittley Factory Sales Representative for more information regarding towing weights and post purchase consult your owner's manual. Consult generic disclaimer for more information. Boat packages on trailers with ratings over 3,500 kg will require a 70mm tow ball, this is available to customers at additional cost at purchase.

\*\*\* Boat trailer packages on a mechanically braked trailer with an ATM of 2,200 kg rating and a GVW rating of 2,000 kgs, require 10% of the package weight to be on the tow ball as down weight. For more information regarding this, please consult your owner's manual or Authorized Whittley Dealer or Whittley Factory Sales Representative for more information.

